

# Big Diameter Dredging Rubber Hose

## 大口径疏浚橡胶管




产品名称	大口径疏浚橡胶管
product name	Big Diameter Dredging Rubber Hose
输送介质	用于港口、码头、海水、淤泥、河沙、排涝用等
conveying medium	Completing a set with dredge boat to clear silt, seawater etc in dredging works
使用温度	-20℃~30℃
temperature available	From -20℃ To 30℃

内径ID		外径OD		工作压力WP		爆破压力BP		真空压力VP		可生产长度
⊙		⊙		⊙		⊙		○		▬
Inside Diameter	Outside Diameter	Working Pressure		Burst Pressure		Vacuum Pressure		Length		
mm	inch	mm	inch	Mpa	bar	Mpa	bar	Kpa	bar	m
152	6"	182	7-1/4"	1.2	12	2.4	24	80	0.8	20
203	8"	233	9-1/5"	1.2	12	2.4	24	80	0.8	20
254	10"	284	11-1/5"	1	10	2	20	80	0.8	10
304	12"	340	13-2/5"	1	10	2	20	80	0.8	6-10
350	14"	390	15-2/5"	1	10	2	20	80	0.8	6-10
450	18"	486	19-1/5"	0.7	7	1.5	15	80	0.8	6-10
550	22"	590	23-3/5"	0.7	7	1.5	15	80	0.8	6-10
600	24"	640	25-3/5"	0.7	7	1.5	15	80	0.8	6-10
700	28"	750	29-3/5"	0.7	7	1.5	15	80	0.8	6-10
800	32"	850	33-1/2"	0.5	5	1	10	80	0.8	6-10
1000	40"	1050	41-1/2"	0.5	5	1	10	80	0.8	6
1200	48"	1250	49-1/5"	0.5	5	1	10	80	0.8	6
1300	52"	1350	53-1/5"	0.5	5	1	10	80	0.8	6

备注: 可根据用户需求, 生产任何规格及性能。  
Remark: We can produce any specification and property according to customers' requirements.

# Roof Prism Rubber Hose

## 直筒式橡胶软管



产品名称	直筒式橡胶软管
product name	Roof Prism Rubber Hose
输送介质	疏浚工程挖泥船配套清理淤泥、海水、沙等。
conveying medium	To work with dredge boat to clear silt, seawater, sand etc in dredging works
使用温度	-20℃~30℃
temperature available	From -20℃ To 30℃
执行标准	HG 2490 93表2
reference standard	HG 2490-93 Form Two

内径ID		外径OD		工作压力WP		爆破压力BP		真空压力VP		编织层数	可生产长度
⊙		⊙		⊙		⊙		○		▬	▬
Inside Diameter	Outside Diameter	Working Pressure		Burst Pressure		Vacuum Pressure		Number Of Piles		Length	
mm	inch	mm	inch	Mpa	bar	Mpa	bar	Kpa	bar	l	m
203	8"	233	9-1/4"	1.6	16	4.8	48	80	0.8	6	6
220	8-3/4"	250	10"	1.6	16	4.8	48	80	0.8	6	6
250	10"	280	11-1/5"	1.6	16	4.8	48	80	0.8	6	6
275	11"	310	12-3/8"	1.6	16	4.8	48	80	0.8	6	6
305	12"	340	13-5/8"	1.2	12	3.6	36	80	0.8	10	6
316	12-5/8"	352	14"	1.2	12	3.6	36	80	0.8	10	6
400	16"	436	17-1/2"	1.2	12	3.6	36	80	0.8	10	6
445	17-1/2"	480	19-1/4"	1.2	12	3.6	36	80	0.8	10	6
460	18-2/5"	500	20"	1.2	12	3.6	36	80	0.8	12	6
530	21-1/5"	584	23-1/5"	1	10	3	30	80	0.8	12	6
560	22-2/5"	614	24-2/5"	1	10	3	30	80	0.8	12	6
584	23-1/5"	644	25-3/4"	1	10	3	30	80	0.8	12	6
610	24-2/5"	670	26-4/5"	1	10	3	30	80	0.8	16	6
700	28"	770	30-4/5"	1	10	3	30	80	0.8	16	6
900	36"	970	38-4/5"	1	10	3	30	80	0.8	16	6

备注: 可根据用户需求, 生产任何规格及性能。  
Remark: We can produce any specification and property according to customers' requirements.